

UNIT 15



Large HD/SD 20 camera production unit

SOUND

Mixer	Lawo mc ² 66 Mark II with 56 faders 192 DSP Channels, 48 local mic/line inputs 32 analog outputs, fiber stagebox with 48 mic/line inputs
Matrix	Lawo Nova HD Core 3K with 8 Ravenna & 16 MADI
Patch	Ghielmetti CSF48
Monitoring	Adam SX3, 5.1 monitoring speakers
Rec / Play	CD, Spot-on, Multi-track 64ch/128ch on request Nuendo
Inserts	TC Electronic DBMax, Waves MaxxBCL, API-2500, TC Electronic System 6000
Embedders	4 x Axon GXT100 with embedding, downconversion and pal coding, 3 deembedders

VIDEO

Cameras	Up to 20x GVG LDK8000 Elite / Sony HDC-2550 camera
Switcher	Sony MVS-7000 HD / 4ME or 50p/2ME switcher 40 inputs and 24 outputs on router 16 resizers, 2 full 3D DVE channels Multistandard 3G/HD/SD
Matrix	Miranda 8280 Hybrid router 288 x 450 with embedders /de-embedders and Madi I/O
Control Sys	VSM
Patch	ADC
Monitorwall	18 Sony PVM2540 OLED monitors with Axon quadplits 9 Sony PVM2540 OLED monitors with Axon quadplits in second production room.
Rec / Play	up to 8 VTR up to 6 EVS XT 4 DVD/Blu-ray recorders
Glue	Axon, Barco Folsom Image Pro HD/3G, Leitch, Snell & Wilcox 6200, As requested

COMMUNICATION

Intercom	Riedel Artist 128 32 x Internal digital intercom panels 6 x External digital intercom panels 8 x 2-wire interfaces 30 x 4-wire interfaces
ISDN/PSTN	2 x Telos Xstream ISDN Codec 1 x Telos One PSTN Interface
Wireless	6 x Motorola GP340 radio 3 x Riedel Riface Motorola base stations Overline systems or Telex BTR-700/800 on request

POWER & DIMENSIONS

Truck 14 x 4,7 x 4 meters ; work area 17 x 7 meters
Power Consumption: 50 kVA on 3-Phase, 400V, 125A
CEE (P17) connector

